

P40D Push Camera



Specifications:

Camera Head

Camera Size: $\Phi 38\text{mm} \times 81\text{mm}$ (main body)

Camera Total Length: 318mm

Sensor: 1/3" Sony CCD, 480 TV-Line

Pixel: 752H * 582V

View Angle: 120°

Transmitter: 512hz built-in(selectable)

Self leveling: Built-in

Focus Distance: 12cm (approx)

Depth-of-Field: 120cm(approx)

Front Lens: Sapphire glass

Water-Proof: 20m Under Water(Camera fix on Cable)

Shell Material: #304 stainless steel

Lighting: Built-in 12×LED(White)

Operating Temperature: -10~50°C/+14~+122°F

Storage Temperature: -20~60°C/+4~+140°F

Cable Wheel

60-120M fiberglass push rod cable with on-screen distance counter

Dia. of push cable: 9mm

LCD Monitor

Screen: 7-inch 16:9 Super bright HD color LCD screen

Resolution: 800x480 RGB
Mirror and Flip: support image mirror, and flip
Video Resolution: 720*576 25fps Max.
Video Encoding: H.264
Photograph: 720*480/720*576
Audio Recording: local sound record
Output: TV and Audio output
External memory: support SD memory card up to 32GB
Data output: USB 2.0 to PC
LED Driver: Built-in dimmer
Play back: Video, Photo and Audio
On-screen date and time
On-screen meter/ft. distance display
Battery Capacity: 7.4V 4400mAh Li-ion Battery
Power Supply: DC 12V input
Life/Charge time: 5/8 hours
Language: English, German, French, Spanish, Italian, Chinese, Japanese, Russian, Portugueses

Optional feature:

- Camera head with built-in 512Hz sonde
- Optional camera skids:
Caster Skid: POM \varnothing 134x83.9. 30mm Wheel
POM Skid: POM \varnothing 78x83.9
Ball Support: POM S \varnothing 60x53.5
Lock Sleeve: POM \varnothing 54.6x38
- Keyboard for text input
- Optional cable length: 60M, 80M, 100M, 120M

Packing details:

- 1 unit in one carton
- Carton G.W.: 23kg-28.8kg
- Carton Measurement: 80 x 36 x 92cm



quakellogic.net



+1-916-899-0391



sales@quakellogic.net