


 **QUAKELOGIC**

# QL-Unitree Go2 EDU+

QUADRUPED ROBOTIC PLATFORM

WITH HESAI XT16 3D LIDAR

 **QUAKELOGIC**



# QL-Unitree Go2 EDU+

## QUADRUPED ROBOTIC PLATFORM

---

The QL-Unitree Go2 EDU+ Quadruped Robotic Platform with Hesai XT16 3D LiDAR is a four-legged robotic platform designed for advanced robotics development, autonomous perception research, AI experimentation, and educational use. The platform combines quadruped mobility, onboard high-performance computing, 3D LiDAR sensing, visual sensing, wireless connectivity, and secondary development support in a compact mobile research system.



# Core Configuration

---

## Core Configuration

- Main CPU: 8-core high-performance processor
- High Computing Power Module: NVIDIA Jetson Orin NX 16GB, 100 TOPS
- Secondary Development Support: Supported
- 3D LiDAR: Hesai XT16 3D LiDAR
- Front Camera: HD camera, 1280 × 720
- Front Camera Lens: Ultra wide-angle, 120° FOV
- Manual Remote Control: Included
- 4G Module: Included
- Foot-End Force Sensor: Included
- Wireless Vector Positioning Tracking Module: Included

## Chassis and Structure

- Dimensions (Standing): 70 × 31 × 40 cm
- Dimensions (Crouching): 76 × 31 × 20 cm
- Weight (with Battery): 15 kg
- Materials: Aluminum alloy and high-strength engineering plastic
- Front Lamp: Included
- Self Retracting Strap: Not included
- 7 inch Pneumatic Wheels: Not supported

## Rotation Ranges

- Body Rotation: ±48°
- Thigh Rotation: -200° to +90°
- Shank Rotation: -156° to -48°

## Mobility and Motion Performance

- Top Speed: 2 m/s
- Typical / Max Payload: 8 kg / 12 kg
- Max Step Height: 16 cm
- Max Slope: 40°
- Max Joint Torque: 45 N·m
- Aluminium Knee Joint Motors: 12 set
- Cooling System: Joint heat pipe cooler
- Wiring: Intra-joint circuit

# Battery and Power

## Battery and Power

- Battery Type: Long Endurance (15000mAh)
- Battery Capacity: 8000 mAh
- Battery Life: 2–4 hours
- Voltage Range: 28V – 33.6V
- Max Working Power: 3000W
- Charger Specs: Fast Charge (33.6V / 9A)
- Overheat / Overcharge / Short Circuit Protection: Yes
- Wireless Charging Pad / Self Charging Board: Yes, compatible

## Perception and Sensing

- iDAR: Hesai XT16 3D LiDAR
- Front Camera Resolution: HD (1280 × 720)
- Front Camera Lens: Ultra wide-angle (120° FOV)
- Foot-End Force Sensor: Included
- Wireless Vector Positioning Tracking Module: Included

# Battery and Power

---

## Interfaces

- USB 3.0
- HDMI
- Ethernet
- External Power Input:  
24V / 12V / 5V
- Power Connector

## Compatible Expansion Options

- Servo Arm: Compatible
- Depth Camera (D435i): Compatible
- Hesai XT16 LiDAR: Compatible
- Mid-360 LiDAR: Compatible
- Wireless Charging Pad / Self Charging Board:  
Compatible

## Connectivity and Communication

- Wi-Fi: Wi-Fi 6, dual band
- Bluetooth: Bluetooth 5.2, 4.2, 2.1
- 4G Module: Included
- Manual Remote Control:  
Included
- Intercom Microphone: Included  
(via app)
- Built-in Speaker: Included (3W)
- Voice Function: Supported

## Software and Development

- Secondary Development: Supported
- Graphical Programme: Supported
- Basic Actions: Supported
- Intelligent detection and avoidance:  
Supported
- Side-Follow System (ISS 2.0):  
Supported
- OTA Upgrade System: Supported
- RTT 2.0 Picture Transmission:  
Supported

## Development Resources

- Provides models, motion control SDK and APIs, as well as perception development interfaces with sample code.

# Technical Specifications

Specification	QL-Unitree Go2 EDU+
Main CPU	8-core high-performance processor
High Computing Power Module	NVIDIA Jetson Orin NX 16GB, 100 TOPS
Secondary Development Support	Supported
Dimensions (Standing)	70 × 31 × 40 cm
Dimensions (Crouching)	76 × 31 × 20 cm
Weight (with Battery)	15 kg
Voltage Range	28V – 33.6V
Battery Type	Long Endurance (15000mAh)
Materials	Aluminum alloy and high-strength engineering plastic
Battery Capacity	8000 mAh
Battery Life	2–4 hours
Max Working Power	3000W
Charger Specs	Fast Charge (33.6V / 9A)
Protection	Overheat / Overcharge / Short Circuit Protection
Payload (Typical / Max)	8 kg / 12 kg
Battery Life	2–4 hours
Top Speed	2 m/s
Max Step Height	16 cm
Max Joint Torque	45 N·m
Knee Joint Motors	12 set
Cooling System	Joint Heat Pipe Cooler
Wiring	Intra-Joint Circuit
Max Slope	40°
Body Rotation	±48°



# Technical Specifications

Thigh Rotation	-200° to +90°
Shank Rotation	-156° to -48°
LiDAR	Hesai XT16 3D LiDAR
Front Camera	HD (1280 × 720), 120° ultra wide-angle
Wireless VPT Module	Included
Foot-End Force Sensor	Included
Wi-Fi	Wi-Fi 6, dual band
Bluetooth	Bluetooth 5.2, 4.2, 2.1
4G Module	Included
Interfaces	USB 3.0, HDMI, Ethernet, External Power Input (24V / 12V / 5V), Power Connector
Manual Remote Control	Included
Intercom Microphone	Included (via app)
Built-in Speaker	Included (3W)
Voice Function	Supported
Basic Actions	Supported
Graphical Programme	Supported
Side-Follow System (ISS 2.0)	Supported
Intelligent Detection, Avoidance	Supported
OTA Upgrade System	Supported
RTT 2.0 Picture Transmission	Supported



# Connect with QuakeLogic – QL-Unitree Go2 EDU+

---

## Corporate Headquarters

QUAKELOGIC INC.  
4010 Foothills Blvd. Suite 103/194  
Roseville, CA 95747, USA

### Factory/Warehouse:

2008 Opportunity Dr. Suite 130,  
Roseville, CA 95678

## Executive Support Line

**+1 (916) 899-0391**

Direct access for technical support, system integration, and robotics platform guidance.

Available Monday – Friday, 9 AM – 5 PM PST

## Strategic Inquiries

**[sales@quakelogic.net](mailto:sales@quakelogic.net)**

For quadruped robotic platforms, AI development systems, and advanced robotics solutions.

## Our Commitment to Advanced Robotics & AI Excellence

### Certified Quality Assurance

Compliant with advanced robotics engineering standards, ensuring reliable performance, safe operation, and long-term stability in AI and autonomous system environments.

### Advanced Mobility & AI Performance

Delivering dynamic quadruped locomotion, real-time AI processing, and high-precision perception with integrated LiDAR and vision systems for autonomous operation.

### Dedicated Client Success

Providing system integration, developer support, SDK guidance, and post-deployment assistance to ensure efficient operation and scalable robotics development.

## Explore Advanced Robotics & AI Solutions



### Scan to Explore Advanced Robotics & AI Solutions

Discover how the QL-Unitree Go2 EDU+ Quadruped Robotic Platform enables advanced robotics development, autonomous navigation, and AI experimentation.

Designed for developers, researchers, and innovation-driven industries, the system delivers powerful onboard computing, real-time perception with LiDAR, and seamless integration into modern robotics ecosystems

Learn more about platform capabilities, development tools, and intelligent robotics systems.

**[www.quakelogic.net](http://www.quakelogic.net)**