ATOM Shake Table

Technical and Mechanical Features



1 - Unmatched Features of ATOM Shake Table



- High-cost benefit ratio
- Affordable laboratory equipment for universities to support hands-on learning
- Extendable warranty period
- EasyTest control software included



- Fully integrated design (including controller and servo-driver)
- Rubber strips for damping and stabilization
- Easy and flexible installation with L brackets



- High total mass capacity
- Large payload area and stroke
- High peak acceleration and velocity
- Wide frequency bandwidth
- Compact and light-weight design
- IP-based, allowing for remote control



2 - Technical Advantages

Specification ATOM Shake Table 18 kg Weight 250 x 250 mm Payload Area ±125 mm Maximum Stroke Maximum Payload @1g **50 kg** Maximum Acceleration @ 7.5 kg 6g Load Maximum Velocity @ 7.5 kg 800 mm/s Load Maximum Operating Frequency 30 Hz



3 - Mechanical Advantages



- Compact Economic Design
- Super Low-Friction Precision Linear Guides
- Integrated Limit Switch for Increased Safety
- Automatic Centering / Home Positioning
- Mounting Holes Grid on the Table
- Detachable Carrying Handle
- Detachable Mounting Accessories with Adjustable Positioning
- Rubber Strips for Damping & Stabilization



4 - SEEING IS BELIEVING!





Please click for product videos or visit youtube.com/quakelogic

Visit our YouTube Channel to watch

- Performance of the shake table
- Training on its control software, EASYTEST

It will always be a pleasure to serve you, and we are here to help you!

For questions please don't hesitate to contact us at

support@quakelogic.net







TO OWN ONE OF OUR SHAKE TABLES, CONTACT NOW sales@quakelogic.net







